


## ELITE GRAPHIC WALL fabric display

ELITE GRAPHIC WALL is constructed of aluminum extrusion and features SEG press fit fabric graphics for hassle free set up. Heavy duty aluminum feet ensure maximum stability. Graphics are printed on premium fabric for vibrant colors. The entire unit disassembles and packs flat in a single rotomolded case for unparalleled protection.

**MODEL #: EGW-48**



### Details

- 1.5" Low-profile aluminum extrusion frame
- Single or double-sided SEG press fit dye-sublimated fabric graphics
- Easy assembly
- Packs in a single rotomolded flat transport case
- Limited Lifetime Warranty
- Made in the USA


### Includes

- 4' x 8' Elite Frame
- Elite Stabilizer Feet
- SEG Front Fabric Graphic
- Elite Tool Kit
- Rotomolded Case

### Dimensions

Assembled unit:  
47.5"w x 95.25"h x 17.5"d  
1206mm x 2419mm x 444mm  
34 lbs / 15.4 kgS

Graphic area:  
47"w x 94.5"h  
1194mm x 2400mm



### Additional information







Set-Up Time: 25-30min  
Lead Time: 10 Days  
Warranty: Limited Lifetime Warranty

### Shipping



Packs in ( 1 ) L-8R1851-01 case  
Shipping dimensions:  
51"h x 18"w x 3"d  
1295mm x 457mm x 76mm  
50 lbs / 22.7 kgS

## EGW-48 PACKAGE CONTENTS

Profile	Label	#	Description
	001	2	1/4" ALUMINIUM OVAL BASE PLATE 17.5" (444.5MM) x 3.15" (80MM)
	002	1	M1307 36" (914.4MM) EXTRUSIONS W/ (2) 45° CUTS & (2) HOLES FOR BASE PLATE
	003	2	M1307 47.5" (1206.5MM) EXTRUSIONS W/ (2) 45° CUTS
	004	2	M1307 36" (914.4MM) EXTRUSIONS W/ (2) 45° CUTS
		4	Z966 90° CORNER INTERNAL CONNECTOR
		2	5/16-18 FLAT HEAD SCREW 2.25" LONG W/ WASHER & WING NUT
		1	35.5"W (908MM) x 47"H (1194MM) SINGLE SIDED DYESUB GRAPHIC W/ SEG WELT ALL 4 SIDES


### 2.



Secure base plate to bottom horizontal extrusions with provided bolt and wing nut

### 3. GRAPHIC

Insert the silicon edge of the fabric into the groove of the extrusions.



Start on the corners, then centers and work your way to corners from center on both directions.

To pull fabric graphic out of extrusion groove, use pull tab on corner


### 4. LIGHT ASSEMBLY (Optional)





Slide light clip into the light. Then place the light into the groove and gently lower it down

### 5. WALL MOUNT (Optional)

Attach wall bracket to top extrusion groove with provided hammerhead screw. Locate position of wall bracket on extrusion (preferably by wood stud) by sliding the bracket on the extrusion and tighten it. Secure the frame to the wall with provided wood screw.



### PACKING DIAGRAM





**10x8**



**8x8**



**6x8**



**6x6**



**4x8**



**4x6**



**4x4**



**3x8**



**3x6**



**3x4**



**3x3**