

SPECIFICATIONS / ASSEMBLY



ELITE GRAPHIC WALL fabric display

ELITE GRAPHIC WALL is constructed of aluminum extrusion and features SEG press fit fabric graphics for hassle free set up. Heavy duty aluminum feet ensure maximum stability. Graphics are printed on premium fabric for vibrant colors. The entire unit disassembles and packs flat in a single rotomolded case for unparalleled protection.

MODEL #: EGW-66











Details

- 1.5" Low-profile aluminum extrusion frame
- · Single or double-sided SEG press fit dye-sublimated fabric graphics
- · Easy assembly
- Packs in a single rotomolded flat transport case
- · Limited Lifetime Warranty
- · Made in the USA


Includes

- · 6' x 6' Flite Frame
- · Elite Stabilizer Feet
- · SEG Front Fabric Graphic
- · Elite Tool Kit
- · Rotomolded Case

Dimensions

Assembled unit: 72"w x 72.25"h x 17.5"d 1829mm x 1835mm x 444mm 40 lbs / 18.1 kgS

Graphic area: 71.5"w x 71.5"h 1816mm x 1816mm



Additional information

Set-Up Time: 25-30min Lead Time: 10 Days

Warranty: Limited Lifetime Warranty




Shipping

Packs in (1) L-8R1851-02 case Shipping dimensions: 51"h x 18"w x 4.5"d 1295mm x 457mm x 114mm 55 lbs / 24.9 kgS



EGW-66 PACKAGE CONTENTS

Profile	Label	#	Description
	001	2	1/4" ALUMINIUM OVAL BASE PLATE 17.5" (444.5MM) x 3.15" (80MM)
П	002	1	M1307 36" (914.4MM) EXTRUSION W/ (1) 45° CUT & (1) HOLE FOR BASE PLATE
П	003	1	M1307 36" (914.4MM) EXTRUSION W/ (1) 45° CUT & (1) HOLE FOR BASE PLATE
п	004	3	M1307 36" (914.4MM) EXTRUSION W/ (1) 45° CUT
П	005	3	M1307 36" (914.4MM) EXTRUSION W/ (1) 45° CUT
==	006	2	Z4400 34.4" (873.8MM) EXTRUSION W/ (1) TENSION LOCK
		4	Z966 90° CORNER INTERNAL CONNECTOR
0 0		5	Z967 STRAIGHT INTERNAL CONNECTOR
7		2	5/16-18 FLAT HEAD SCREW 2.25" LONG W/ WASHER & WING NUT
		1	71.5"W (1816MM)x 71.5"H (1816MM) SINGLE SIDED DYESUB GRAPHIC W/ SEG WELT ALL 4 SIDES



3. Repeat above steps to connect all spliced

4. Slide corner connector (Z966) into both sides of

horizontal extrusions.Turn each screw enough to

6. Slide vertical extrusions onto corner connectors of top horizontal extrusion. Turn each screw

connectors of bottom horizontal extrusion into inner channel of vertical extrusions and tighten the screws to secure frame extrusions together.

extrusions together.

extrusions together.

hold connector in place.

enough to hold connector in place.

7. Finish frame assembly by sliding corner

