

LCD MOUNT INSTALLATION INSTRUCTIONS


LB-K01, LB-K02, LB-K03, LB-K04, LB-K05 SERIES

Drywall Installation

IMPORTANT: The weight of the LCD requires installation into a wood stud. Failure to do so may result in damage or injury.


Use a stud finder to locate a wood stud where you want to install your mount. It is recommended that you verify the location of the stud using a small nail or an awl. You should use the center of the stud.

After the stud has been located, place the wall piece against the wall with the hook towards the bottom. Secure the wall piece using one Dry wall Screw, but do not completely tighten yet. Using the integrated bubble guide, carefully adjust the wall piece until it is level. Insert the remaining screw and tighten both screws.



Concrete/Brick Installation

Begin by placing the wall piece into position against the wall with the hook towards the bottom. Using the integrated bubble guide to keep it level, mark off the holes that will be used for securing the mount and place the wall piece aside. Next, drill holes using an electric drill and 5/16" (8mm) masonry bit. Remove any excess dust from the holes and insert a Concrete Anchor into each hole. If necessary, use a hammer to lightly tap each anchor into place so that they are flush with the wall.



Once both anchors are in place, put the wall piece back into position. Attach the wall piece using the Drywall Screws provided. Make sure both screws are secure.

Step 2 Attaching the Arm to the LCD

IMPORTANT: Make sure the LCD is unplugged before starting this step of the installation and never lay the LCD face down as this may damage the viewing surface.

Before attaching the arm piece of the mount to your LCD, you must first determine which hardware to use. Do this by examining the back of the LCD. If your LCD has a flat back, use the M4x12mm Bolts. If your LCD has a recessed back, use the longer M4x30mm Bolts. After you have determined the appropriate bolts, use them to attach the arm piece of the mount to the back of your LCD. Be careful not to over-tighten the bolts.

Step 3 Final Installation and Operation.

Final Installation

To complete the installation, simply slide the arm piece with your LCD attached into the wall piece. The plastic tab on the top of the wall piece should click indicating that the arm piece is secure. If you need to remove the arm piece, push in on the tab and slide the arm up.

