

POWERPLUS™ WWA 40W FIXTURE — I SERIES



UNLEASH THE POWER OF COLORGLO™ LEDs

J&J
ELECTRONICS, INC.

This slim and attractive fixture offers the advantages of high-output WWA LED technology for even the most demanding architectural environments.

Product Summary

The PowerPlus WWA 40W I Series is a compact, linear color temperature changing LED fixture with an internal DMX decoder, driver and power supply.

This fixture features 24 – 1 watt LEDs mounted at 0.4" spacing to ensure an even and homogenous color output. It is ideal for interior or exterior applications where efficient, maintenance-free white light is required.


Mounting

Mounting options include trunion brackets for 180° orientation or metal clips for flush mounting the flat bottom surface of the fixture to any surface using standard screws.

Power & Control

The PowerPlus WWA 40W fixture is capable of interfacing directly to any standard DMX 512 control device. It uses on board dip switches to set any 3 sequential channels (from 1 – 512) to control WWA functions. DMX input is via a standard 5 pin XLR male connector. An XLR female output is provided for connection in a daisy chain configuration. A termination dip switch is also provided.

The PowerPlus WWA 40W E Series is powered by 100 – 240 VAC / 50-60Hz with cord or conduit connection options.



ADDRESSABLE DMX COLOR TEMPERATURE CONTROLLABLE WHITE LIGHT FROM 2200° TO 6500°K

KEY FEATURES:

- User adjustable white light color temperature
- Sealed fixture for exterior or interior use
- Available with a choice of optics from very narrow to wide flood

IDEAL FOR:

- Commercial and residential interior and exterior task lighting
- Cove lighting
- Wall washing
- Retail and museum displays
- Other uses suited for efficient, maintenance-free white light

FEATURES & BENEFITS

- ✦ Easy installation and operation with no additional power supply or external DMX addressing or distribution module
- ✦ Sealed fixture - to withstand weather conditions
- ✦ Uniformly spaced LED configuration for even and consistent output
- ✦ Choice of optic viewing angle - 15°, 30°, 60°, or (for wide light distribution) 120°
- ✦ Adaptable to multiple lighting applications — with a wide variety of mounting options
- ✦ LEDs offer flicker free start up and operation in cold environments
- ✦ Maintenance free lifespan up to 100,000 hours



ColorGlo™

Manufactured by:  J&J Electronics • **800.735.4553** • 949.455.4460 • www.colorgloledlighting.com

POWERPLUS™ WWA 40W FIXTURE — I SERIES

J&J ELECTRONICS, INC.

PRODUCT SPECIFICATIONS

Dimensions	
Length	12.3" / 312.42mm
Width	4.8" / 121.92mm
Height	2.5" / 63.5mm
Input Voltage	100 – 240 VAC / 50-60 Hz
Input Current	0 - 400mA@120VAC
LED Lumen Output – WWA (with 120° optic viewing angle)	0 – 1000
Input Power Connect	Standard UL listed cord and plug or 1/2" WT EMT
LEDs	8 Amber, 8 Warm White, 8 Cool White – 1W
Color Temperature	2200°K – 6500°K
DMX Input	5 pin XLR
DMX Output	5 pin XLR
DMX Standard	USITT DMX 512 1990
DMX Range	1 – 512
Termination	User selectable – 120 ohms
Fixture Listing	UL Pending
Internal Power Supply Listing	IP66, CE, FCC, UL, CUL
Internal Power Supply	Class 2 Output
PCB flame rating	UL 94-V0
Housing	All weather sealed, black anodized aluminum extrusion, white powder coated end and face plates, polycarbonate lens

BUILDING A PART NUMBER

LLS-PP40-WWA-I- [Mounting Option] - [Power Connect] - [Optic Viewing Angle]

MC (mounting clips) **P** (standard plug/cord set) 15°, 30°, 60°, or 120°

TB (trunion brackets) **C** (EMT conduit connect)

Example: **LLS-PP40-WWA-I-TB-P-120**



Also available without trunion
(optional end-plates for stationary mounting)

Contact J&J Electronics for pricing information.

Manufactured by:



J & J ELECTRONICS, INC.

35 Hammond

Irvine, CA 92618 USA

800.735.4553 • 949.455.4460

Fax: 949.455.4474

www.colorgloledlighting.com



ColorGlo™

©2006 J&J Electronics, Inc. All rights reserved. PowerPlus, ColorGlo and IntelliGlo are trademarks of J&J Electronics, Inc.

Rev. 051506